


RESİM	AÇIKLAMA			
	<p>Curtis controller; 24V/80AH free maintenance battery; DC driving motor; mechanical steering; H channel steel mast; PU wheels; External intelligent charger</p>	<p>MİMA MBD1230 1.2 TON 3.000 MM ASANSÖRLÜ ELEKTRİKLİ İSTİFLEME MAKİNASI</p>		

AÇIKLAMA :

TESLİMAT : HEMEN TESLİM - İŞLETME TESLİM

GARANTİ SÜRESİ: 2 yıl 2000 SAAT (Hangisi önce dolarsa) Aküler 3 yıl 6000 SAAT (Hangisi önce dolarsa)

Electric pallet stacker MBD

1,1	Manufacturer		MİMA	
1,2	Model		MBD12	
1,3	Power type		Battery	
1,4	Driving style		Walkie	
1,5	Rated load	Q(kg)	1200	
1,6	Load center	C(mm)	500	
1,7	Wheelbase	y(mm)	1200	

Weights

2,1	Service Weight(incl.battery)	kg	560	
-----	------------------------------	----	-----	--

Wheels

3,1	wheel type		PU	
3,2	Load wheel size	mm	Φ80×70	
3,3	Drive wheel size	mm	Φ210×70	
3,4	Stabilizing wheel size	mm	Φ125×50	
3,5	Number of wheels,front/rear(x=drive wheel)		2/1x+1	
3,6	Wheel base,drive-bearing side	b ₁₀ (mm)	/	
3,7	Wheel base, load-bearing side	b ₁₁ (mm)	400	

Size

4.1	Mast closed height	h ₁ (mm)	2030	
4.2	Lift height	h ₃ (mm)		
4.3	Mast extended height with load-backrest	h ₄ (mm)	3510	
4.4	Handle height(min/max)	h ₁₄ (mm)	800/1200	
4.5	Minimum height of fork surface	h ₁₃ (mm)	85	
4.6	Overall length	l ₁ (mm)	1750	
4.7	Overall width	b ₁ (mm)	800	
4.8	Fork size	l/e/s(mm)	1150/160/60	
4.9	Fork outside width	b ₅ (mm)	560*	
4.10	Mast ground clearance	m ₁ (mm)	30	
4.11	Aisle width (pallet 1000x1200)Load center C500mm	A _{st} (mm)	2050	
4.12	Right-angle stacking aisle width (pallet 800x1200)Load center C600mm	A _{st} (mm)	2100	
4.13	Turning radius	W _a (mm)	1440	

Function

5,1	Driving speed, load/unloaded	km/h	3.5/4	
5,2	Lifting speed,load/unloaded	mm/s	110/180	
5,3	Lowering speed,load/unload	mm/s	130/160	
5.4	Maximum climbing ability, load/unloaded (S2-5min)	%(tanθ)	3/6	
5.5	Braking method		Electromagnetic	

Drive

6,1	Drive motor power (S2-60min)	kw	0,75	
6,2	Lift motor power, (S3-15%)	kw	2	
6,3	Battery, voltage/rated capacity	V/Ah	2×12/80	
6,4	Battery weight	kg	50	
6,5	steering system		Mechanical steering	

Others

7,1	Battery replacement method		Battery	
7,2	Mast series		Single cylinder duplex mast	

DİĞER

7,1	Battery replacement type		Hoisting	
7,2	Lithium battery voltage/capacity	V/Ah	24/200	
6.6	Direksiyon sistemi			

Other

7.2	AC kaldırma motoru. (S3-15%)	kw		
-----	------------------------------	----	--	--

